



PROFILE

Lift Systems

Specifics:

60 foot wide lift system with 16 lines 4' on center.
 Lifts an Austrian or Braille drape up to 30 feet high.
 Proven Reliability.
 Fixed speed / Up, Down and Stop
 Operates on Single Phase 220v power.

A La Carte or Turn-key System:

Compatible with any curtain which has lift lines on 4 foot centers.
 16 fully connected lines spanning 60 continuous running feet.
 Single Controller for Up, Down and Stop commands.
 Centralized Motor.
 Ships in one crate with (operational) drape attached.

Why You'll Love It:

A motorized drape reveal with an exotic detailed drapery does not have to be a designer fantasy. This system is compact, user friendly and affordable. Take your show or event to the next level.....
what ever you plan to reveal - make it special

Famous Friends:

Our Ivory Austrian on this lift system is tough act to follow....
Luckily the act was Lady Gaga!
 One of the most (in)famous artists in the industry, she wowed audiences with her performance "in between" our spectacular curtain moves.



Contact:
 310-639-7000





INSTRUCTIONS

Lift Systems



Lift Systems Instructions and Tips

1. Mount the motor
 - A. On 12" truss use 4 pipe clamps with the saddles welded to them. Attach 2 on each side of the motor. Slide the pins on the top hole to hold the motor in place.
 - B. On 24" truss use the supplied spacer board and ratchet strap to secure it to the truss.
2. Pull hoses and drape out of the box and lay on floor parallel to the truss.
3. The brackets are labeled left and right. Starting at the motor, work your way outwards in sequential order. Attach brackets with the lift points on 4' centers (the swivel burgers can adjust to accommodate various truss sizes and angles. The bracket does not have to be straight as long as the hose is taut.)
- 4a. Most of the lift points attach by pushing the securing pin through the pulley block.
- 4b. Some points attach by screwing in the hinged point to the bracket.
5. Attach 220 single phase power to the controller with the 5-pin twistlock cable provided.
6. Connect controller to the motor with the 19 pin socapex cable provided.
7. Fly the truss up to trim height.
8. Run the curtain down, then re-tie the weights to adjust them to about 6" off the floor.

Rent What? pre-sets the lower limits to the drape height.

Tips:

- **Do not run unit without weight on the lines.****
- **Do not let the weights touch the floor.****
- **Always keep tension on the lines to prevent lines from tangling.****
- **Max power draw is 10 amps.****



Contact:
310-639-7000